

Bumpon™



;
SJ-5000 • SJ-5200 • SJ-5300 • SJ-5400
SJ-5500 • SJ-5700 • SJ-6100

2003

3M™ Bumpon™ -

3M™ Bumpon™ -

3M™ Bumpon™

3

Bumpon™.

3M™ Bumpon™ SJ-5518,
3M™ Bumpon™ SJ-5508,
3M™ Bumpon™ SJ-5523, 4 1,
3M™ Bumpon™ SJ-5514, 4 1,

64 .

64 .





SJ-5000 • SJ-5200 • SJ-5300 • SJ-5400
 SJ-5500 • SJ-5700 • SJ-6100

	<p>Bumpon SJ-5302, SJ5402*</p> <p>7.9 2.2</p>	<p>Bumpon SJ-5306, SJ-5406*</p> <p>9.5 3.8</p>	<p>Bumpon SJ-5303</p> <p>11.1 5.0</p>	<p>Bumpon SJ-5312, SJ-5412*</p> <p>12.7 3.5</p>
	<p>Bumpon SJ-5003</p> <p>11.1 5.0</p>	<p>Bumpon SJ-5027, SJ-5327**</p> <p>16.0 7.9</p>	<p>Bumpon SJ-5017, SJ-5317**</p> <p>19.0 9.6</p>	<p>Bumpon SJ-5009, SJ-5309**</p> <p>22.3 10.1</p>
	<p>Bumpon SJ-5012</p> <p>12.7 3.5</p>	<p>Bumpon SJ-5001, SJ-5301**</p> <p>12.7 3.5</p>	<p>Bumpon SJ-5744, SJ-5344**</p> <p>19 4.0</p>	<p>Bumpon SJ-5514</p> <p>20.6 13.1</p>
	<p>Bumpon SJ-5007, SJ-5307**</p> <p>10.2 2.5</p>	<p>Bumpon SJ-5008, SJ-5308**</p> <p>12.7 3.1</p>	<p>Bumpon SJ-5018, SJ-5318**</p> <p>12.7 5.8</p>	<p>Bumpon SJ-5023, SJ-5323**</p> <p>20.5 7.6</p>

Bumpon™



SJ-5000 • SJ-5200 • SJ-5300 • SJ-5400
 SJ-5500 • SJ-5700 • SJ-6100

				
	Bumpon SJ-5705	Bumpon SJ-5077, SJ-5377	Bumpon SJ-5532	Bumpon SJ-5201*, SJ-5202*
	31.75 6.1	16.5 4.0	47.7 16.7	11.0 3.2(Bumpon SJ-5201) 1.6(Bumpon SJ-5202)

		Bumpon™ SJ-5000 SJ-5500 SJ-5700	Bumpon™ SJ-5300 SJ-5400	Bumpon™ SJ-5200	SJ-6100
	ASTM-D2240	70	75	25	70
, %	ASTM-D2632	30	5	20	30
	ASTM-D1894	>1 >1 0.9-1.4	>1 >1 0.9-1.4	- - -	>1 >1 0.9-1.4
,	ASTM-D412	4.1	5.1	0.8	4.1
, %	ASTM-D412	100	65	100	100
, /	ASTM-D1000	7800	14500	-	7800
	5° - 52°				
	: -34° - 66° : 105°				
	5% 25%	24 (1)			

